

NEW EF Deburring Machine with brushless motor

Conforms to latest EC Regulations with brushless motor

Feel the difference:

- Efficient deburring and chamfering of single pieces or batch produced parts in machining or assembly plants.
- In use next to the production machine reduces idle time and thereby overall costs.
- Milling of chamfers, corner radius or front surfaces on workpieces made of steel, stainless steel, aluminium, nonferrous metals, plastics, hardwood, etc.

1000's IN USE!

Universal deburring and chamfering machines with hardened steel table 10 x 10 inches (250 x 250mm)

Features:

- Easy operation
- Powerful double insulated motor for high output.
- Spindle speed infinitely varaible for optimum cutting speed, chip removal and excellent surface finish of chamfers or radius in any material.
- Chamfer height infinitely adjustable by means of a micrometer screw with 0.05 mm (0.002") reading.



In the box:

Includes essential tool kit with the 230v 50hz model (part no. 921.400.111)

Get in touch:

PHONE: (07793) 025 070 or (01256) 893 863

 ${\sf ONLINE:}\ \textbf{www.allsolutionproducts.com}\ {\sf EMAIL:}\ \textbf{sales@allsolutionproducts.com}$





NEWEF Deburring Machine

with brushless motor

Technical specification:

Power supply 230v 50hz

110v 60hz

Table surface 250 x 250 mm

Motor power rating

Input500 WattOutput350 Watt

Cutter speed

(continuously variable) 12,000 RPM to

30,000 RPM Chamfer height

(45° angle) infinitely adjustable for steel 0 to 2 mm for non ferrous 0 to 3 mm

Angle

"B" on work piece 15°/30°/45°/60°

Radius

"R" on work piece 0.25 to 3.0 mm

Net weight approx. 19.5 kg

Areas of use:

Machine Shops
Tool rooms
Fabrication & Welding
Sheet Metal
Sign & Nameplates
Pump manufacturers
Component manufacturers
Plastic & Nylon products
Washers
Steel/Aluminium Parts









Conforms to latest EC Regulations

with brushless motor









WORLDWIDE DELIVERY

PHONE: (07793) 025 070 or (01256) 893 863

ONLINE: www.allsolutionproducts.com EMAIL: sales@allsolutionproducts.com ALL SOLUTION PRODUCTS LTD 4 Skylark Rise, Whitchurch, Hants, RG28 7SY

VAT GB 815 9778 80 Registered in Cardiff No. 4882493





Schallberger Facette Star EFG

The largest universal deburring machine

12 x 20 inches
Heat-treated steel table

Application's STAR

- Efficient deburring of workpieces with large, flat surfaces.
- Troublefree deburring of sheet metal, front panels, etc. due to large table surface.
- Milling of chamfers, corner radii or front surfaces on workpieces made of steel, stainless steel, aluminium, non-ferrous metals, plastics, hardwood, etc.

Features:

- Solid, portable work shop machine.
- The machine, provided with 4 rubber shoes, is held in working position on the bench by its own weight.
- Ready for use in seconds, set next to the production machine to reduce extra time and thereby overall costs.
- Large table surface, 12" x 20" (300 x 500 mm).
- Drive motor and control unit identical to SCHALLBERGER FACETTE STAR EF.

In the box:

- Open end wrench 13 mm
- Cranked open end wrench 19 mm
- Collet with nut, Ø 6 mm
- Collet with nut, Ø 8 mm
- Guide-rule p/n 921.900.565
- Milling cutter Ø 10 mm x 450 Part No. **921.1090.00**
- Milling cutter for contours
 Ø 6 mm x 450 with ball bearing
 Part No. **921.0690.40**
- Cutter set-up gauge Part No. 921.900.900

Get in touch:

PHONE: (07793) 025 070 or (01256) 893 863

ONLINE: www.allsolutionproducts.com EMAIL: sales@allsolutionproducts.com






Schallberger Facette Star EFG

The largest universal deburring machine


2 x 20 inches Heat-treated steel table

Tool holders




Collet for cutters Clamping holder for guide-fingers

Front view



- Length (housing) 500mm
- Range of adjustment ± .160" (4mm)
- Overall Length 590mm

View from right side



Total height 280mm Total width 300mm

Technical Data:

	EUNUPE
■ Power supply	230 V, 50 Hz
Motor power rating: input: output:	500 Watt 270 Watt
■ Cutter speed, continuously variable	13 000 to 28 000 RPM
Chamfer height, 'H' angle 45° infinitely adjustable, for steel: for non ferrous	0 to 2 mm 0 to 3 mm
■ Table surface	300 x 500 mm
■ Angle 'B' on workpiece	15° / 30° / 45° / 60°
■ Radius 'R' on workpiece	.25mm to 3.0mm34 kg
net weight	30 Kg

FIIROPE

WORLDWIDE DELIVERY

PHONE: (07793) 025 070 or (01256) 893 863

ONLINE: www.allsolutionproducts.com EMAIL: sales@allsolutionproducts.com





Schallberger Facette Star 500 Chamfering Machine

With
sliding table
and infinitely
variable cutting
speed

Save time, save money...

- To deburr and chamfer safely, efficiently without counter-burs, on single pieces or batch produced parts.
- Using it next to the production machine reduces extra time and thereby overall costs.
- The sliding table system eliminates scratches on the workpiece surfaces, the workpiece remains firm on the table by the ball bearings.
- The bearing system allows for uniform movement of workpieces up to 50kg (110lbs) across the cutter eliminating chatter and the need of repetitive operations.
- Milling of chamfers on workpieces of steel, stainless steel, non-ferrous metals, aluminium, plastic materials, hardwood, etc.
- An absolute necessity for the tool and die-maker, mould-maker, machinery builder, mechanical workshop, synthetic resin and electronic industry.



Features:







Gauge to square small items (standard access) p/n 923.500.031

Get in touch:

PHONE: (07793) 025 070 or (01256) 893 863

ONLINE: www.allsolutionproducts.com EMAIL: sales@allsolutionproducts.com





Schallberger Facette Star 500 Chamfering Machine



Standard accessories:

BENCH TYPE MACHINE:

- 1p/n 923.419.000 Cutter head
- 5 p/n 923.419.100 Carbide Inserts
- 1 p/n 923.500.031 Gauge
- 1 Moulded cable assembly
- 1 Set of wrenches

MACHINE ON TROLLEY:

- 1p/n 923.419.000 Cutter head
- 5 p/n 923.419.100 Carbide Inserts
- 1 p/n 923.500.150 Grinding head
- 1 p/n 923.500.031 Gauge
- Trolley with drawer and suction device
- 1 Moulded cable assembly
- 1 Set of wrenches

Technical Data:		EUROPE
■ Power supply		230 V, 50 Hz
Motor power rating: input: output:		650 Watt 500 Watt
■ Cutter speed, continuously variable		1200 to 8000 RPM
■ Chamfer height, infinitely adjustable		01 to 5 mm
■ Workpiece:	thickness min: weight max:	1 mm 20 kg
Stroke of sliding table		500 mm
■ Surface area,	length: width:	760 mm 125 x 50 mm
■ Net weight, approx.		51 kg
Part No. for bench type machine:		923.400.500
Part No. for machine on trolley:		923.400.505

WORLDWIDE DELIVERY

PHONE: (07793) 025 070 or (01256) 893 863

ONLINE: www.allsolutionproducts.com EMAIL: sales@allsolutionproducts.com

